



## TECHNICAL DATA SHEET

### ▲ HARDFLOOR PROTECTOR

#### APPLICATIONS

Temporary protection of surfaces of the following materials:

Wood, tile, stone, ceramic and vinyl.

*Do not use on PVDF, Plastisol, Polyurethanic paints.*

*Not suitable for protection against corrosion, humidity or chemical solvents.*

Due to the high variety and evolution of floor lacquers, clear coats and cleaning materials, we strongly recommend that a test is carried out on a small area of the surface to be protected in order to ensure full compatibility with our adhesive system.

Our self adhesive protective films are designed for temporary surface protection against debris, spillages and potential scratches; they are not designed for protection against corrosion, humidity or chemicals. Their applications are very diverse and the conditions of use can vary from one enterprise to another, for this reason we request the client to test the product and carry out a trial, prior to use.

We cannot be responsible for the misuse of the product, nor for the consequences of their usage for non-recommended applications. The product guarantee is generally limited to the replacement of the defective product and does not cover consequential claims.

#### STORAGE AND UTILISATION:

The recommended maximum usage of Packexe Floor Protector is four to six weeks.

The film can be stored for between six and twelve months, in original packaging at room temperature and in dry conditions.

#### OUTLINES

FILM TYPE	Polyethylene (LDPE)
AVERAGE THICKNESS	50 micron
COLOUR	Clear
ADHESIVE TYPE	Acrylic solvent base
ADHESION TO STEEL	280 cN/cm
LONGITUDINAL TENSILE STRENGTH	>1 daN/cm
TRANSVERSAL TENSILE STRENGTH	>0.7
LONGITUDINAL MAX. ELONGATION	>200 %
ELONGATION	TRANSVERSAL MAX. >470 %