

FLEXIBLE CRACK REPAIR FILLER



Advantages

- + Highly flexible
- + Excellent adhesion to substrates
- + Fibre reinforced for moving cracks
- + Waterproof
- + No fibre tape or fabric required
- + White

GENERAL INFORMATION

Description

Ready mixed flexible crack repair filler

Intended use

- Interior/exterior
- Repairs to reoccurring cracks due to structural movement

Manual application



USE

DILUTION Ready mixed

APPLICATION

Conditions Do not apply at temperatures of below + 5°C or above + 35°C, or at a relative humidity of above 80% H.R.

Equipment Filling knife, blade

Equipment cleaning With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

APPLICATION THICKNESS 3 mm

AVERAGE CONSUMPTION 1 L/m² per mm thickness

SUBSTRATES Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, old painted substrates, previously printed wood and derivatives.
Substrates must be hard, cohesive, clean, sound and dry according to the local standards.

OVERCOAT Primer, filler, conventional paint, light-weight wall coverings



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



FLEXIBLE CRACK REPAIR FILLER

TECHNICAL DATA



COMPONANTS	Polymer base aqueous phase coat mix, mineral fillers, additives 70% of raw materials of natural origin (Calcium carbonate, clay, pigment, water)
DENSITY	1,4 ± 0,1
pH	8 ± 1
COLOUR	White
WORKING TIME AT 20°C	Unlimited
WAITING TIME BEFORE OVERCOATING	Once completely dry
CLASSIFICATION	NF T 36-005 - Family IV, class 4b
NORM	NF EN 16566
V.O.C.	< 1 g/l (ready mixed)

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on www.beissier.eu or www.quickfds.com

PACKAGING 600 ml bucket

STORAGE 12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. + 30°C) sun and moisture. Close well after use. Store in original packaging

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : January 2024

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

Beissier

Applying excellence

BEISSIER | Becket House - 1 Lambeth Palace Road - LONDON - SE1 7EU

Customer service : ☎ 020 7092 6696 | contact@beissier.eu