

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ralston Siloxan Mat BW
Revision date : 17-04-2020
Print date : 17-04-2020

Version (Revision) : 3.0.0 (2.0.2)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Ralston Siloxan Mat BW

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified use: Paints and lacquers, for further details check Product Data Sheet/ Label. Uses advised against: On substrates not mentioned in the Product Data Sheet/ Label.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Ralston Colour & Coatings B.V.
part of Royal Van Wijnhe Verf

Street : Russenweg 14

Postal code/city : 8041 AL ZWOLLE

Telephone : +31 (0)38-4291100

Telefax : +31 (0)38-4210414

Contact : MSDS@ralstoncolour.com

1.4 Emergency telephone number

+31 (0)38-4291100(During office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

This mixture is not classified as dangerous according to Regulation (EC) 1272/2008.

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P285	In case of inadequate ventilation wear respiratory protection.
P501	Dispose of contents/ container according to national/ international regulations.

Special rules for supplemental label elements for certain mixtures

EUH208	Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE ; REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1).May produce an allergic reaction.
EUH210	Safety data sheet available on request.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ralston Siloxan Mat BW
Revision date : 17-04-2020
Print date : 17-04-2020

Version (Revision) : 3.0.0 (2.0.2)

Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List.

Hazardous ingredients

1-(2-BUTOXYPROPOXY)PROPAN-2-OL ; EC No. : 246-011-6; CAS No. : 24083-03-2

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H312

Dimethyl siloxane ; CAS No. : 63148-62-9

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT / KEROSENE - UNSPECIFIED ; EC No. : 265-149-8; CAS No. : 64742-47-8

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

In case of skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do NOT use solvents or thinners.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Carbon dioxide (CO₂) Extinguishing powder Water mist

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Exposure to decomposition products may cause a health hazard. Use suitable breathing

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ralston Siloxan Mat BW
Revision date : 17-04-2020
Print date : 17-04-2020

Version (Revision) : 3.0.0 (2.0.2)

apparatus.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Avoid breathing vapours. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Only use the material in places where open light, fire and other flammable sources can be kept away.

Protective measures

Measures to prevent aerosol and dust generation

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Environmental precautions

Do not allow to enter drains or water courses.

Specific requirements or handling rules

Electrical equipment should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. No sparking tools should be used.

Advices on general occupational hygiene

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Avoid inhalation of dust from sanding. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8).

7.2 Conditions for safe storage, including any incompatibilities

Comply with the health and safety at work laws. Observe label precautions.

Technical measures and storage conditions

Never use pressure to empty container.

Packaging materials

Always keep in containers of same material as the original one. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Requirements for storage rooms and vessels

Only allow access to authorised staff.

Hints on joint storage

Do not store together with

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ralston Siloxan Mat BW
Revision date : 17-04-2020
Print date : 17-04-2020

Version (Revision) : 3.0.0 (2.0.2)

Keep away from

Keep away from sources of ignition - No smoking.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

None

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protection equipment

Eye/face protection

Use safety eyewear designed to protect against splash of liquids.

Skin protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Hand protection

Use chemical-resistant gloves (according to EN 374).

By short-term hand contact : For short-term contact use gloves with adequate chemical protection, thickness \geq 0.2 mm, performance level \geq 1 (breakthrough time \geq 10 minutes).

By long-term hand contact : For prolonged and repeated contact use gloves with adequate chemical protection, thickness 0.4 mm, performance level 6 (breakthrough time \geq 480 minutes).

Suitable material : NBR (Nitrile rubber)

Additional hand protection measures : Always ensure that gloves are free from defects and that they are stored and used correctly. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. After contact with skin, wash immediately with plenty of water and soap.

Respiratory protection

If workers are exposed to dust/ fumes/ aerosols in concentrations above the exposure limit, they must use appropriate, certified respirators(NEN-EN 140:1998/C1:2000, CE-marking) or independent breathing protection. The respiratory protection filter class must be at least suitable for the maximum concentration of the contamination (gas / vapor / dust particles) that may arise during use. We recommend using an AX filter according to EN 371 or EN14387. Always read the manufacturer's instructions before use. Pay attention to the wearing time limit of the respiratory mask! In case of exceedance of the specified maximum concentration, a compressed air mask must be used.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Safety characteristics

Physical state :		Liquid
Odeur:		Typical paint odour.
Odeur threshold:		Unknown
pH :	approx.	9
Melting point/freezing point :	<	0 °C
Initial boiling point and boiling range :	(1013 hPa) >	100 °C
Lower explosion limit :		No data available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ralston Siloxan Mat BW
Revision date : 17-04-2020
Print date : 17-04-2020
Version (Revision) : 3.0.0 (2.0.2)

Upper explosion limit :			No data available	
Vapour pressure :	(50 °C / 122 °F)		No data available	
Vapour density:			No data available	
Density :	(20 °C / 68 °F)	approx.	1,48	g/cm ³
Solvent separation test :	(20 °C / 68 °F)		No data available	
Auto-ignition temperature :		>	388	°C
Decomposition temperature :			No data available	
Viscositeit KU :	(20 °C / 68 °F)	approx.	118	KU
Flow time :	(20 °C / 68 °F)	>	90	s
Evaporation rate (n-butylacetate = 1):			No data available	DIN-cup 4 mm DIN 53170
Flash point :		>	100	°C
Flammability:			No data available	
Explosive properties:			None	
Solubility:			No data available	
Oxidising properties:			None	

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

Carbon dioxide. Carbon monoxide Nitrogen oxides (NOx).

SECTION 11: Toxicological information

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of Regulation (EC) 1272/2008 and not classified.

11.1 Information on toxicological effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

SECTION 12: Ecological information

There are no data available on the mixture itself. Do not allow to enter drains or water courses.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ralston Siloxan Mat BW
Revision date : 17-04-2020
Print date : 17-04-2020

Version (Revision) : 3.0.0 (2.0.2)

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Do not allow to enter drains or water courses. Wastes and emptied containers should be classified in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.8 Additional information

Air transport (ICAO-TI / IATA-DGR)

The "viscosity exemption" provision does not apply to air transport.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None

15.2 Chemical safety assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ralston Siloxan Mat BW
Revision date : 17-04-2020
Print date : 17-04-2020

Version (Revision) : 3.0.0 (2.0.2)

16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP]

16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM = American Society of Testing and Materials (US)
CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)
DNEL = Derived No-Effect Level
DT50 = Time for 50% loss; half-life
EbC50 = Median effective concentration (biomass, e.g. of algae)
EC50 = Median effective concentration
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)
ErC50 = Median effective concentration (growth rate, e.g. of algae)
EWC = European Waste Catalogue
IATA = International Air Transport Association
IC50 = Concentration that produces 50% inhibition
IMDG = International Maritime Dangerous Goods Code
IMO = International Maritime Organization
LC50 = Concentration required to kill 50% of test organisms
LD50 = Dose required to kill 50% of test organisms
LEL = Lower Explosive Limit/Lower Explosion Limit
LOAEL = Lowest observed adverse effect level
MRL = Maximum Residue Limit
NOAEL = No Observed Adverse Effect Level
NOEC = No observed effect concentration
NOEL = No Observable Effect Level
OEL = Occupational Exposure Limits
PBT = Persistent, Bioaccumulative or Toxic
PNEC = Previsible Non Effect Concentration
STEL = Short-Term Exposure Limit
TWA = Time-Weighted Average
vPvB = Very Persistent and Very Bioaccumulative

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H319	Causes serious eye irritation.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ralston Siloxan Mat BW
Revision date : 17-04-2020
Print date : 17-04-2020

Version (Revision) : 3.0.0 (2.0.2)
