

## SHAKE WELL BEFORE USE

Danish Oil contains tung oil and other special ingredients which penetrate deep into all types of timber, drying to a hard, durable and water resistant seal. The oil primes, seals and finishes all woods, including oak, teak, mahogany and pine. It does not leave a surface film to chip or scratch. May also be used as a primer before painting and varnishing. Excellent for use on all turned work including wooden handles of kitchen equipment and tops of storage jars. Rustins Danish Oil conforms to The Articles in Contact with Food Regulations and to the Toys (Safety) Regulations 1995, BS:EN71 Part 3. We recommend Rustins Floor Oil for interior floors.

## Preparation

The surface must be clean, sanded smooth and free from contaminants like wax and dirt. For best results apply to dry, sound wood with a moisture content between 12-20%. Do not apply to green timber. Oily woods (e.g. Teak, Iroko) should be cleaned thoroughly with white spirit before application of Danish Oil. Exterior wood requires a minimum of 3 coats applied liberally and not wiped off. To improve the penetration and durability dilute the first coat 20% with white spirit. If applying Danish Oil to veneered doors, it is advisable to check with the door manufacturer before proceeding. Exterior wood will require regular re-oiling, especially on horizontal surfaces and in very exposed conditions. Oak and softwoods are prone to weather staining caused by moisture activating mould spores present naturally in the wood. It is advisable to treat the wood with Rustins Advanced Clear Wood Preserver before applying Danish Oil. Extra coats of Danish Oil are required to effectively seal these timbers. If in doubt use Rustins Outdoor Clear Varnish or Rustins Flexterior. Bare wood may be dyed if required with Rustins Wood Dye. If a natural open grain is not required such as with oak, then use Rustins Grain Filler prior to oiling.

## Application

Using a clean soft cloth or brush apply liberally, then wipe off the excess after a few minutes. For a superior smooth finish the final coat may be applied using a plastic scouring pad, rubbing in the direction of the grain, wiping away the surplus with a soft cloth or paper towels. New or bare wood should be oiled 3 times initially.

## Re-Coating Time

Allow 4 to 8 hours between applications depending on the temperature and humidity.

## Maintenance

When applying to previously oiled wood, the surface should be cleaned and any wax removed using white spirit or Rustins Surface Cleaner. Wipe away the solution formed with clean paper towels, prior to re-oiling. If the surface develops a slight gloss, this can be removed by rubbing with grade 00 or 000 steel wool and either wax polish or white spirit finishing off with a soft cloth. If compatibility with a previously coated surface is not known, then test by applying to a small area first.

## Coverage

1 litre covers approximately 14 square metres per coat depending on the absorbency of the wood.

## Cleaning

Remove excess product from brushes before cleaning whilst wet with white spirit or Rustins Brush Cleaner. Hard brushes can be cleaned with Rustins Brush Restorer.

## Important

Rags used for oiling must be laid out flat to dry or destroyed, otherwise they may catch fire due to spontaneous combustion.

## Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

## Storage

Store in a cool dry place with lid tightly closed.

### HEALTH AND SAFETY:

Contains Hydrocarbons, C9 - C11, n alkanes, isoalkanes, cyclics, <2% aromatics. COBALT 6 (13586-82-8), 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE (55965-84-9). May produce an allergic reaction. Flammable liquid and vapour. May cause respiratory irritation. Toxic to aquatic life with long lasting effects. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear eye protection, face protection, protective gloves. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Call POISON CENTRE if you feel unwell. UFI: MP2N-QRQC-5FOY-EMAO Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



EU Limit value for this product (CAT A/I): 700g/l (2010). This product contains max 650g/l VOC.

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



# Rustins



Rustins – producing expert wood finishes since 1924.



# Rustins

## The Original Danish Oil Natural, low lustre finish For all types of wood



# Rustins

Ideal for  
Tables  
Chairs  
Wooden Furniture  
Doors  
Dado Rails  
Wood Panelling  
Window Frames/Sills  
Wooden Worktops



1 Litre e

## For interior and exterior use