

Rustins new formula **Strypit** is a non-caustic dichloromethane-free gel suitable for removing multiple coats of paints and varnishes applied to wood, metal, glass, stone and masonry surfaces. **Strypit** works best when applied liberally and allowed to penetrate after two applications. The gel consistency permits effective use on vertical surfaces.

DIRECTIONS FOR USE

Use appropriate personal protection including gloves and eye protection. Shake tin well and remove cap carefully holding the tin away from face. Brush on a liberal coat with a dabbing action. Leave until paint begins to soften or blister, usually for 5 to 10 minutes, and test with a stripping knife or scraper. Apply a second liberal coat and ensure that this is worked into the blisters or softened paint. Leave for further 35 to 40 minutes. Remove the blistered, softened paint with a stripping knife or scraper. If any paint or varnish remains, repeat the process. Use steel wool to remove paint from curved surfaces. Wash down the surface thoroughly with water and allow to dry completely. On wood, white spirit can be used to wash down to avoid raising the grain. On old paint or very heavy applications **Strypit** can be left on longer to maximise penetration.

The rate of coverage is approximately 5 square meters per litre.

CLEANING UP

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses. Clean brushes with warm soapy water. Store in a cool dry place with lid tightly closed away from sources of ignition. Protect from frost.

NOTE: Not suitable on fibreglass, rubber and some plastics.

HEALTH AND SAFETY

Highly flammable liquid and vapour. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed.

Wear eye protection, face protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Store in a well-ventilated place. Keep cool.

Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: R9RG-90AJ-P210-3107

Please refer to Product Data Sheet for full information at www.rustins.co.uk



DANGER


For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom or rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade,
Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



Rustins

Effective & Easy
Stripping



1. Brush on one coat of **Strypit** liberally.



2. Leave **Strypit** to penetrate.

Removes
multiple coats

•
Non drip – ideal for
vertical surfaces

•
Does not contain
dichloromethane

•
Non caustic

•
Water and
white spirit
washable

500ml e

Rustins

Strypit

PAINT & VARNISH STRIPPER

STRIPS PAINT, VARNISH,
POLYURETHANE, EMULSION,
FRENCH POLISH & LACQUER

FOR USE ON WOOD, METAL,
GLASS & PLASTER

Rustins


Effective & Easy
Stripping



3. Dab on a second application liberally.



4. Remove softened paint or varnish with scraper.



500ml e

Rustins

Strypit

PAINT & VARNISH STRIPPER

**STRIPS PAINT,
VARNISH,
POLYURETHANE,
EMULSION,
FRENCH POLISH &
LACQUER**

**FOR USE ON WOOD,
METAL, GLASS &
PLASTER**

Rustins

**Effective & Easy
Stripping**

1. Spray on a liberal coat **Strypit** and leave until paint starts to soften or blister.
2. Wait for 5 - 10 minutes then test with a stripping knife or scraper.
3. Apply a second coat of **Strypit** and ensure that this is worked into the blisters/softened paint. Leave for a further 35-40 minutes.
4. Remove softened paint with a stripping knife or scraper

500ml e

Rustins new formula **Strypit** is a non-caustic dichloromethane-free gel suitable for removing multiple coats of paints and varnishes applied to wood, metal, glass, stone and masonry surfaces. **Strypit** works best when applied liberally and allowed to penetrate after two applications. The gel consistency permits effective use on vertical surfaces.

DIRECTIONS FOR USE

Use appropriate personal protection including gloves and eye protection. Shake tin well and remove cap carefully holding the tin away from face. Spray on a liberal coat and leave until paint begins to soften or blister, usually for 5 to 10 minutes, and test with a stripping knife or scraper. Apply a second liberal coat and ensure that this is worked into the blisters or softened paint. Leave for further 35 to 40 minutes. Remove the blistered, softened paint with a stripping knife or scraper. If any paint or varnish remains, repeat the process. Use steel wool to remove paint from curved surfaces. Wash down the surface thoroughly with water and allow to dry completely. On wood, white spirit can be used to wash down to avoid raising the grain. On old paint or very heavy applications **Strypit** can be left on longer to maximise penetration. The rate of coverage is approximately 5 square meters per litre.

CLEANING UP

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses. Clean brushes with warm soapy water. Store in a cool dry place with lid tightly closed away from sources of ignition. Protect from frost.

NOTE: Not suitable on fibreglass, rubber and some plastics.

HEALTH AND SAFETY

Extremely flammable aerosol. Pressurised container: may burst if heated. Causes serious eye damage. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe vapour/spray. Wear protective gloves/ protective clothing/ eye protection/ face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/ doctor. Use only outdoors or a well ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

CONTAINS 1,3-DIOXOLANE

UFI: R9RG-90AJ-P210-3107

Please refer to Product Data Sheet for full information at www.rustins.co.uk



DANGER


For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom or rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland.
Tel: +353 1 - 832 3300

3 650

**UK
CA**

**SOLVENT
ABUSE
CAN KILL
INSTANTLY**



5 015332 004317